

Installation Instructions

CageX™ Ladder Cage Extension Net



INCOR

The InCord CageX Ladder Cage Extension Net System provides worker protection within the exposed area between the ladder cage and the platform handrail.

The CageX System consists of a high-strength HTTP UV resistant fiber net, bound on four sides with polyester rope. Six chinch straps secure the net between the ladder cage and hand rail. Read all Instructions before assembly.



Note: Chinch Strap is threaded from the bottom up as shown with the "PRESS" tab on top.



Step 1. Center the CageX Net over the ladder cage support and fasten with one chinch strap at the center as shown with the letter "A". Spread the net along the cage support and attach the left and right corners as shown with chinch straps. Spread the net along the hand rail and install two chinch straps at the left and right corners. Attach the last chinch strap at the bottom center and secure it to the hand rail.

Step 2. Tighten each chinch strap, tie the loose strap end in a knot, then cut the trailing end off with shears.

CageX Inspection Procedure: The CageX Net should be inspected annually. Two types of failures should be noted. First, inspect the net itself; any broken "bars" /meshes in the net should be noted and if they occur, the net should be replaced. The six chinch straps should be inspected; if any are missing, cut or damaged, they should be replaced. If any employee using the ladder notices either of these deficiencies they should be reported to maintenance and the appropriate action taken.

